

CWPVC-6

APRIL, 2010

PLEASE ORDER BY PART NUMBER.

	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	PALLETS PER T.L.	PART NO.
10' BELLED END SOLVENT WELD SDR-35 SEWER PIPE ASTM D-3034	3" SOLID	3.250	3.064	.093	63.47	1000	32	53075
	3" PERF	3.250	3.064	.093	63.47	1000	32	53080
	4" SOLID	4.215	3.975	.120	106.51	900	24	53112
	4" PERF	4.215	3.975	.120	106.51	900	24	53119
	6" SOLID	6.275	5.915	.180	238.40	350	24	53179
	6" PERF	6.275	5.915	.180	238.40	350	24	53196

PERFORATIONS ARE 2 ROWS OF 1/2" HOLES ON 5" CENTERS 120° APART

20' BELLED END SOLVENT WELD SDR-35 SEWER PIPE ASTM D-3034	4" SOLID	4.215	3.975	.120	106.51	1200	16	53117
	4" PERF	4.215	3.975	.120	106.51	1200	16	53121
	6" SOLID	6.275	5.915	.180	238.40	700	12	53184
	6" PERF	6.275	5.915	.180	100.80	700	12	53201
	8" SOLID	8.400	7.920	.240	224.66	400	12	53253
	8" PERF	8.400	7.920	.240	402.48	400	12	53262

PERFORATIONS ARE 2 ROWS OF 1/2" HOLES ON 5" CENTERS 120° APART

14' GASKET JOINT SDR-35 SEWER PIPE ASTM D-3034 WHITE	4"	4.215	3.975	.120	109.84	1260	18	53725
	6	6.275	5.915	.180	245.85	490	18	53784
	8	8.400	7.920	.240	441.75	280	18	53805

20' GASKET JOINT SDR-35 SEWER PIPE ASTM D-3034 WHITE	4"	4.215	3.975	.120	108.84	1200	16	53734
	6	6.275	5.915	.180	243.62	700	12	53794
	8	8.400	7.920	.240	436.81	400	12	53814

14' & 20' LAYING LENGTHS. INSERTION DEPTH RING IS MARKED ON THE BEVELED SPIGOT END OF PIPE.

GASKETS ARE REINFORCE RUBBER RING AND PERMANENTLY INSTALLED IN AN INTEGRAL BELL.

MADE OF COMPOUNDS CONFORMING TO ASTM D-1784 WITH CELL CLASSIFICATION OF 12364.

REFER TO ASTM D-2321 FOR PROPER INSTALLATION PROCEDURES OF SDR-35 SEWER PIPE.

4" - 8" SDR-35 SEWER PIPE IS CERTIFIED TO THE UNIFORM PLUMBING CODE BY NSF INTERNATIONAL.

NSF® sewer U.P.Code

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD · PHOENIX, AZ 85009 · TELEPHONE (602) 269-5161

WAREHOUSE: 1930 W. WHITESBRIDGE ROAD · FRESNO, CA 93706 · TELEPHONE (559) 486-1840

www.cresline.com