


MAY, 2010

CWPVC-10

PLEASE ORDER BY PART NUMBER.

ADDITIONAL 10% CHARGE IF NOT ORDERED IN PALLET QUANTITIES.

PVC SCH 40 RIGID ELECTRICAL CONDUIT  ELECTRICAL UL 651	SIZE	O.D.	I.D.	MIN. WALL	WEIGHT PER 100'	FEET PER PALLET	BELL END LGTH.	PART NO.
	1/2"	.840	.622	.109	16.12	3000	10'	58015
3/4	1.050	.824	.113	21.50	4400	10'	58025	
1	1.315	1.049	.133	31.89	3600	10'	58035	
					7200	20'	58030	
1 1/4	1.660	1.380	.140	43.24	3300	10'	58045	
					6600	20'	58040	
1 1/2	1.900	1.610	.145	51.65	2250	10'	58055	
					4500	20'	58050	
2	2.375	2.067	.154	69.85	1400	10'	58065	
					2800	20'	58060	
2 1/2	2.875	2.469	.203	110.80	930	10'	58075	
					1860	20'	58070	
3	3.500	3.068	.216	145.13	880	10'	58085	
					1760	20'	58080	
4	4.500	4.026	.237	206.63	570	10'	58095	
					1140	20'	58090	

PVC SCH 40 ELECTRICAL CONDUIT IS PRODUCED IN 10' & 20' LENGTHS WITH BELL END.

PVC SCH 40 ELECTRICAL CONDUIT IS GRAY IN COLOR.

PVC SCH 40 ELECTRICAL CONDUIT CONFORMS TO: UL 651 INCLUDING 90° C RATING
NEMA TC 2
SUNLIGHT RESISTANT

% OF TRUCKLOAD PER PALLET		
SIZE	%/TL	%/TL
	10' LGTH.	20' LGTH.
1/2	0.9	--
3/4	2.1	--
1	1.7	3.4
1 1/4	2.6	5.2
1 1/2	2.5	5.0
2	2.1	4.2
2 1/2	2.3	4.6
3	2.9	5.8
4	3.0	6.0

CRESLINE - WEST, INC.

CORPORATE HEADQUARTERS: 600 CROSS POINTE BOULEVARD · EVANSVILLE, IN 47715 · TELEPHONE (812) 428-9300

PLANT: 3747 W. BUCKEYE ROAD · PHOENIX, AZ 85009 · TELEPHONE (602) 269-5161

WAREHOUSE: 1930 W. WHITESBRIDGE ROAD · FRESNO, CA 93706 · TELEPHONE (559) 486-1840

www.cresline.com