



**NT
FLEXIBLE PIPE**

FORM NO. 161-NT SPECIFICATIONS
 PRICES ARE LISTED ON FORM MLP-1.
 INSERT FITTINGS LISTED ON FORM NUMBER 166.
 STAINLESS STEEL CLAMPS LISTED ON FORM NUMBER 865.
 PLEASE ORDER BY PART NUMBER.



AUGUST, 2007

NT 160 SIDR-7 POTABLE WATER	SIZE	I.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
	3/4"	.824	.118	15.38	100	15005
400					15010	
1		1.049	.150	24.87	100	15015
					300	15020
1 1/4		1.380	.197	43.04	100	15025
					300	15030

NT 100 IRRIGATION PIPE SIDR-11.5 POTABLE WATER	1/2"	.622	.060	5.66	100	01005
					400	01010
	3/4"	.824	.072	8.93	100	01015
					400	01020
	1	1.049	.091	14.44	100	01035
					300	01040
	1 1/4	1.380	.120	24.80	100	01055
					300	01060
	1 1/2	1.610	.140	33.91	100	01075
					250	01080
	2	2.067	.180	56.01	100	01090
					200	01095

NT 80 IRRIGATION PIPE SIDR-15 POTABLE WATER	3/4"	.824	.060	7.31	100	04005
					400	04010
	1	1.049	.070	10.85	100	04020
					300	04025
	1 1/4	1.380	.092	18.67	100	04035
					300	04040
	1 1/2	1.610	.107	25.40	100	04050
					250	04055
	2	2.067	.138	42.12	100	04060
					200	04065

ALL CRESLINE NT PIPE IS PRODUCED FROM PE 3608 MATERIAL AND CONFORMS TO ASTM D 2239.

CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
 264 Silver Spring Rd.
 2100 South 35th St.
 3801 East Hwy. 31

Evansville, IN 47715
 Mechanicsburg, PA 17050
 Council Bluffs, IA 51501
 Corsicana, TX 75109

812-428-9350
 717-766-2566
 712-322-2294
 903-872-8475

www.cresline.com

Fax 812-428-9353
 Fax 717-697-2371
 Fax 712-322-6673
 Fax 903-872-7732

**PRESSURE RATING
FOR CRESLINE FLEXIBLE PIPES
AT VARIOUS TEMPERATURES
ALL SIZES**

DEGREE °F	73.4° F AND BELOW	100° F	120° F	140° F
NT 160	160	125	125	100
NT 100	100	80	80	60
NT 80	80	60	60	50

PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY FOR A LONG TIME WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.

CRESLINE NT FLEXIBLE PLASTIC PIPE MAY BE USED ON SUBMERSIBLE PUMPS OF 1 HP OR LESS.

MAXIMUM DEPTH SETTINGS TO WATER LEVEL IN FT. @ 60°F			
CRESLINE PE FLEXIBLE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
NT 160	300'	280'	260'
NT 100	180'	155'	135'
NT 80	125'	100'	75'



CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
264 Silver Spring Rd.
2100 South 35th St.
3801 East Hwy. 31

Evansville, IN 47715
Mechanicsburg, PA 17050
Council Bluffs, IA 51501
Corsicana, TX 75109

812-428-9350
717-766-2566
712-322-2294
903-872-8475

www.cresline.com

Fax 812-428-9353
Fax 717-697-2371
Fax 712-322-6673
Fax 903-872-7732