




FORM NO. 761 THD SPECIFICATIONS

JUNE, 2010

PLEASE ORDER BY PART NUMBER

| PVC SCH-80 THREADED DROP PIPE ASTM D-1785  | SIZE | O.D. | MIN. WALL | WEIGHT PER 100' | MAX PSI 73°F | FEET PER PALLET | PALLETS PER T.L. | PART NO. |
|--|------|-------|--------------|-----------------------|--------------------|-----------------------|------------------------|-------------|
| | 1" | 1.315 | .179 | 41.23 | 315 | 2600 | 44 | 43056 |
| | 1¼ | 1.660 | .191 | 57.06 | 260 | 2000 | 44 | 43078 |
| | 1½ | 1.900 | .200 | 69.19 | 235 | 2360 | 40 | 43085 |
| | 2 | 2.375 | .218 | 95.89 | 200 | 1860 | 32 | 43100 |

| PVC SCH-120 THREADED DROP PIPE ASTM D-1785  | SIZE | O.D. | MIN. WALL | WEIGHT PER 100' | MAX PSI 73°F | FEET PER PALLET | PALLETS PER T.L. | PART NO. |
|---|------|-------|--------------|-----------------------|--------------------|-----------------------|------------------------|-------------|
| | 1" | 1.315 | .200 | 45.21 | 360 | 2600 | 44 | 43350 |
| | 1¼ | 1.660 | .215 | 63.12 | 300 | 2000 | 44 | 43370 |
| | 2 | 2.375 | .250 | 108.10 | 240 | 1860 | 32 | 43390 |

| WW25 MACHINED COUPLING | | | |
|---|------|-------------|--------|
|  | SIZE | PART NO. | QTY. |
| | 1 | 85250 | 10/100 |
| | 1¼ | 85252 | 10/100 |
| | 1½ | 85253 | 15 |
| | 2 | 85254 | 10 |
| THREAD X THREAD EXTRA HEAVY - SCH120 FOR USE ON THREADED SCH 80 DROP PIPE | | | |



CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
264 Silver Spring Rd.
2100 South 35th St.
3801 East Hwy. 31

Evansville, IN 47715
Mechanicsburg, PA 17050
Council Bluffs, IA 51501
Corsicana, TX 75109

812-428-9350
717-766-2566
712-322-2294
903-872-8475

www.cresline.com

Fax 812-428-9353
Fax 717-697-2371
Fax 712-322-6673
Fax 903-872-7732

PVC THREADED DROP PIPE DEPTH GUIDELINES

| PVC THREADED SCHEDULE 80 PIPE HORSEPOWER RATINGS - DEPTH CHART | | | | | | |
|---|--------|--------------------------|--|--------|--------|-----------------|
| SIZE | MAX HP | RECOMMENDED FITTINGS | PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH | | | TORQUE ARRESTOR |
| | | | 40 PSI | 50 PSI | 60 PSI | |
| 1" | 1.5 | EXTRUDED COUPLINGS | 610' | 590' | 570' | USE OVER 150' |
| 1 1/4" | 2 | EXTRUDED COUPLINGS | 475' | 455' | 435' | USE OVER 150' |
| 1 1/2" | 5 | STEEL OR BRASS COUPLINGS | 435' | 415' | 395' | USE OVER 150' |
| 2" | 7.5 | STEEL OR BRASS COUPLINGS | 350' | 325' | 300' | USE OVER 150' |

| PVC THREADED SCHEDULE 120 PIPE HORSEPOWER RATINGS - DEPTH CHART | | | | | | |
|--|--------|--------------------------|--|--------|--------|-----------------|
| SIZE | MAX HP | RECOMMENDED FITTINGS | PUMPING LIMITATIONS - BASED ON SHUT-OFF SWITCH | | | TORQUE ARRESTOR |
| | | | 40 PSI | 50 PSI | 60 PSI | |
| 1" | 1.5 | EXTRUDED COUPLINGS | 700' | 675' | 650' | USE OVER 150' |
| 1 1/4" | 2 | EXTRUDED COUPLINGS | 570' | 545' | 520' | USE OVER 150' |
| 2" | 7.5 | STEEL OR BRASS COUPLINGS | 435' | 415' | 395' | USE OVER 150' |



CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
264 Silver Spring Rd.
2100 South 35th St.
3801 East Hwy. 31

Evansville, IN 47715
Mechanicsburg, PA 17050
Council Bluffs, IA 51501
Corsicana, TX 75109

812-428-9350
717-766-2566
712-322-2294
903-872-8475

www.cresline.com

Fax 812-428-9353
Fax 717-697-2371
Fax 712-322-6673
Fax 903-872-7732